

**VESI**BAFFLE CLOUD

ezoBord



ezoBord Baffle Clouds are a stylish addition to any ceiling, easy to install, and can be customized through the use of wide array of standard ezoBord colors.

A new generation of ceiling baffles - sound dampening, free-hanging and designed for style.

Stylish ezoBord Baffle Clouds are a series of sound absorbing suspended panels that redefine interior open spaces.

The rolling Vesi model helps you to bring a designer look into open offices, restaurants and public spaces, that will help reduce noise and reverberation. Adjustable to various heights and angles, and installed from deck, ceilings, drywall, standard T bar suspension systems.

# STANDARD SHAPE




| PART NUMBER       | WIDTH        | LENGTH       | MAX HEIGHT   | THICKNESS  | BAFFLES |
|-------------------|--------------|--------------|--------------|------------|---------|
| bfc-ves-4747-0709 | 47" (1192mm) | 47" (1192mm) | 7¾" (197mm)  | 3/s" (9mm) | 7       |
| bfc-ves-4747-1109 | 47" (1192mm) | 47" (1192mm) | 11½" (292mm) | 3/8" (9mm) | 7       |
| bfc-ves-4747-0712 | 47" (1192mm) | 47" (1192mm) | 7¾" (197mm)  | ½" (12mm)  | 7       |
| bfc-ves-4747-1112 | 47" (1192mm) | 47" (1192mm) | 11½" (292mm) | ½" (12mm)  | 7       |
| bfc-ves-9595-0709 | 95" (2413mm) | 95" (2413mm) | 7¾" (197mm)  | 3/8" (9mm) | 13      |
| bfc-ves-9595-1109 | 95" (2413mm) | 95" (2413mm) | 11½" (292mm) | 3/8" (9mm) | 13      |
| bfc-ves-9595-0712 | 95" (2413mm) | 95" (2413mm) | 7¾" (197mm)  | ½" (12mm)  | 13      |
| bfc-ves-9595-1112 | 95" (2413mm) | 95" (2413mm) | 11½" (292mm) | ½" (12mm)  | 13      |

Please note that all dimensions are nominal, supplier reserves the right to adjust sizing without prior notification.



# **COMPONENTS**



# RECOMMENDED HARDWARE (NOT INCLUDED)





## **CUSTOMIZABLE PARAMETERS**

## **Geometric Properties**

Length, height, width and baffle spacing

## **Material Thickness**

3/8" (9mm) or 1/2" (12mm)

## **Baffle Thickness**

3/8" (9mm) or 1/2" (12mm)

## Color

Each slab can be manufactured with different color

## **Digital Print**

Custom graphics and textures can be printed on baffles

## Scalability

Larger areas can be covered with invisible joints



#### **SPECIFICATIONS**

#### Shapes

1 standard shape available in two sizes.

#### Sizes

Available in two widths and lengths:

- · 47" (1192mm) × 47" (1192mm)
- 95" (2413mm) × 95" (2413mm)

Available in two maximum heights:

- · 73/4" (197mm)
- · 11½" (292mm).

#### **Thickness**

Available in two thicknesses:

- · 3/8" (9mm) | ±0.5mm
- · ½" (12mm) | ±0.5mm

#### Composition

100% PET (min. %50 recycled content)

#### **Product Variances**

Variation in fiber mix and colour may occur. All products will be supplied within commercial tolerances.

#### Cleaning

Remove dust and dirt with a stiff plastic bristle brush. Distilled water can be used to remove stains. Always use a soft, clean cloth and blot dry. Vacuuming works great as well.

### Fire Testing

- · North America:
  - ASTM E-84 Class A\*
  - CAN ULC S102-10
- · Europe and UK:
  - EN13501-1: 2007

#### Installation

All Baffle Clouds are adjustable to various heights and angles and are quick and easy to install from a deck or through a suspended T bar ceiling using the included universal suspension framework. Check with local building code authorities for allowable applications.

#### Acoustics

Refer to ASTM C423 test chart for specific absorption rates/frequency.

- ¾" (9mm): NRC 0.75 (subject to mounting conditions and geometrical properties)
- ½" (12mm): NRC 0.85 (subject to mounting conditions and geometrical properties)

### **USGBC LEED v4 Credits**

While individual products do not 'earn' LEED credits, ezoBord can contribute to the following LEED v4 Credits. Please refer to the USGBC LEED credit guides for detailed requirements.

- EQc9 for enhancing acoustic performance
- MRc3 BPDO for sourcing of raw materials for recycled contribution
- EQc6 interior lighting for surface reflectance (lighter color options).

#### **Environment**

Made of polyester fiber, min. 50% of which comes from recycled water bottles which contributes to LEED MR Credit and BREEAM Health and Wellbeing, Materials points due to recycled content, acoustic performance, and low emitting materials. No VOC's: CDPH v1.2 and REACH SVHC Compliant.



<sup>\*</sup> Upon request, 1/2"(12mm) sheet material is treated with USA origin post-production flame retardant to Class A surface burning characteristics. Post sheet production FR treatment does not contain any Red List Restricted Chemicals and complies with California Proposition 65. Contact customer service for technical information, test data and safety data sheets for flame retardant.



# NOISE REDUCTION - 3/8" (9mm)

### Constructed from

3/8" (9mm) ezoBord

# **Baffle Spacing**


105/8" (269.88mm)

### **Baffle Height**

121/8" (307.97mm)

## SOUND ABSORPTION COEFFICIENTS (ASTM C423-17)

| NRC  | SAA  | 125  | 250  | 500  | 1000 | 2000 | 4000 |
|------|------|------|------|------|------|------|------|
| 0.60 | 0.59 | 0.21 | 0.33 | 0.49 | 0.63 | 0.91 | 1.10 |



FREQUENCY (Hz)

# NOISE REDUCTION - 1/2" (12mm)

#### Constructed from

½" (12mm) ezoBord

## **Baffle Spacing**


10½" (266.7mm)

## **Baffle Height**

12" (304.8mm)

## SOUND ABSORPTION COEFFICIENTS (ASTM C423-17)

| NRC  | SAA  | 125  | 250  | 500  | 1000 | 2000 | 4000 |
|------|------|------|------|------|------|------|------|
| 0.70 | 0.70 | 0.22 | 0.40 | 0.56 | 0.74 | 1.08 | 1.27 |



FREQUENCY (Hz)



# STANDARD COLORS - 3/8" (9mm)



# STANDARD COLORS - 1/2" (12mm)





## **CONNECT WITH US**

www.ezoBord.com







in linkedin.com/company/ezobord

# ezoBord is a registered trademark of iVekter Inc.

## **USA**

Ayrsonics Midwest LLC 170 Prairie Lake Rd East Dundee, IL 60118 1-800-517-0686 sales@mw.ayrsonics.com

## **CANADA**

Ayrsonics Inc. 825 Trillium Drive Kitchener ON N2R 1J9 1-844-441-1122 sales@ayrsonics.com

## UNITED KINGDOM

ezoBord UK LTD Unit 20 Westwood Business Park Margate, Kent, CT9 4JJ +44 7981 111236 sales@ezobord.co.uk